

THERMOELECTRIC MODULE TYPE	BASIC CHARACTERISTICS						DIMENSIONS, mm		
	Uoc V	Rin Ohm	Rload Ohm	Wload W	Uload V	Am W/C	Hot side	Cold side	Heigth
TMG-18-5.0-1.1	0.94	0.028	0.028	7.8	0.47	1.05	40x40	40x40	4.1
TMG-18-5.0-1.3	0.94	0.034	0.34	6.5	0.47	0.88	40*x0	40x40	4.3
TMG-18-5.0-1.6	0.94	0.041	0.041	53	0.74	0.71	40x40	40x40	4.6
TMG-111-1.4-1.2*	5.8	2	2	4.2	2.9	0.57	35x40	35x40	3
TMG-127-1.0-1.3	6.6	4.4	4.4	2.4	3.3	0.33	30x30	30x30	3.6
TMG-127-1.0-1.6	6.6	5.5	5.5	2	3.3	0.27	30x30	30x30	3.8
TMG-127-1.0-2.0	6.6	7	7	1.6	3.3	0.21	30x30	30x30	4.2
TMG-127-1.4-1.2	6.6	2.3	2.3	4.8	3.3	0.85	40x40	40x40	3.4
TMG-127-1.4-1.6	6.6	3	3	3.7	3.3	0.5	40x40	40x40	3.8
TMG-127-1.4-2.5	6.6	4.7	4.7	2.3	3.3	0.31	40x40	40x40	4.7
TMG-127-2.0-1.3	6.6	1.2	1.2	9	3.3	1.26	50x50	50x54	3.6
TMG-127-2.0-1.6	6.6	1.4	1.4	7.5	3.3	1.02	50x50	50x54	3.8
TMG-241-1.0-1.3	12.5	8.4	8.4	4.7	6.3	0.63	40x40	40x40	3.6
TMG-241-1.0-1.6	12.5	10.3	10.3	3.8	6.3	0.51	40x40	40x40	3.8
TMG-241-1.4-1.2	12.5	4.2	4.2	9.4	6.3	1.28	54.4x54.4	54.4x57	3.4
TMG-254-1.4-1.2	13.2	4.4	4.4	10	6.6	1.3	40x80	44x80	3.4
TMG-254-1.4-1.6	13.2	5.9	5.9	7.4	6.6	1	40x80	44*80	3.8
TMG-450-0.8-1.0	234	20	20	6.8	11.7	0.93	54.4x54.4	54.4x57	3.4